

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 March 2004 (11.03.2004)


PCT

(10) International Publication Number
WO 2004/021742 A3

- (51) International Patent Classification⁷: **H05B 1/02** (74) Agents: **EITAN, PEARL, LATZER & CO-
HEN-ZEDEK** et al.; 2 Gav Yam Center, 7 Shenkar
Street, 46725 Herzlia (IL).
- (21) International Application Number:
PCT/IL2003/000700
- (22) International Filing Date: 25 August 2003 (25.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
151504 27 August 2002 (27.08.2002) IL
- (71) Applicant (for all designated States except US):
THERMION LTD. [IL/IL]; 12 Ha'Sadna St., 61050
Tel Aviv (IL).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **MAGAL, Yosef**
[IL/IL]; Tarshish 1, 44856 Kdumim (IL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: IMPROVEMENTS IN THERMOSTAT FOR WATER BOILER



(57) Abstract: A thermal control device (10) for electrically powered appliances, in particular a thermostat to protect against overheating of a hot water boiler. The thermostat having a structure (26) supporting a first (20) and second (18) electric switches disposed in series between an electric power supply and an electric heating element, an extended length first bimetal device (14) being arranged for thermal at least indirect contact with water being heated, a second bimetal device (16) disposed inside the first bimetal device and acting to open the second switch if the second bimetal device reaches a second temperature higher than a first temperature due to the failure of the first bimetal device to open the first switch

WO 2004/021742 A3